









**Recommended for all
Pressurized Hose Connections**

Spring loaded galvanized steel safety cables loop over each hose to prevent the hoses from whipping in case of accidental separation of the couplings.

	PART NO	HOSE SIZE	DESCRIPTION
			
<u>HOSE TO HOSE</u>			
	27WC-1	1/2" - 1-1/4"	1/8" Cable x 20" Long
	27WC-15	1" - 2-1/2"	3/16" Cable x 28" Long
	27WC-2	1-1/2" - 3"	1/4" Cable x 38" Long
<u>HOSE TO TOOL</u>			
	27WT-1	1/2" - 1-1/4"	1/8" Cable x 20" Long
	27WT-2	1-1/2" - 3"	1/4" Cable x 38" Long

Wire Cable Specifications

1/8"	Cable	7 x 7	Galvanized Steel Cable	590 kgs Breaking Strain	200 psi Max Working Pressure
3/16"	Cable	7 x 19	Galvanized Steel Cable	1730 kgs Breaking Strain	200 psi Max Working Pressure
1/4"	Cable	7 x 19	Galvanized Steel Cable	2500 kgs Breaking Strain	200 psi Max Working Pressure



WC-1



WC-15



WC-2

National Equipment Corporation

1806 Buchanan St.
Brenham, Tx 77833

TEL: 979/830-8030
800/933-2316

FAX: 979/830-0983
800/447-2194