PRODUCT BULLETIN	Full-Flow Sandblast Couplings

Full Port couplings for High Volume applications.
35% More Volume with 1-1/2" hose.
Higher Pressure Rating.
Less Gasket Wear.

Q-2X
for 1" Hose

Q-3X
for 1-1/4" Hose

Q-4X
for 1-1/2" Hose

Q-6X
for 2" Hose

SB-3X
for 1-1/2" Pipe

SB-4X
for 2" Pipe

Aluminum or Brass
Maximum recommended operating pressure: Brass = 175 psi, Aluminum = 150 psi
These couplings are extra large and will not interchange with smaller sizes.

DIMENSIONS



Part No.	Hose Size	Hose OD	A Gasket ID	B Length
Q-2X	1"	1-7/8"	1-3/4"	3"
Q-3X	1-1/4"	2-5/32"	1-3/4"	4"
Q-4X	1-1/2"	2-3/8"	1-3/4"	4"
Q-6X	2"	2-7/8"	1-3/4"	4-1/2"
SB-3X	1-1/2"	NPT	1-3/4"	Threaded
SB-4X	2"	NPT	1-3/4"	Threaded

National Equipment Corp.
1806 Buchanan St.
Brenham, TX 77833

TEL: 979/830-8030
800/933-2316

FAX: 979/830-0983
800/447-2194